



BA

Usability

- Low weight and compact design
- Very bright colour display

Technology

- Ultra fast switch-off time (< 5 µs)
- Direct measurement of output voltage
- Measurement of silicone-, mineral- and ester oils
- Housed in a metal case for proper RFI/EMC shielding

Communications

- Bluetooth connection
- USB Flash Drive
- Intuitive control concept

b2 High-Voltage
is a business of

b2 electronic GmbH

Riedstraße 1
6833 Klaus
AUSTRIA

Tel. +43 (0)5523 57373
Fax + 43 (0)5523 57373-5

www.b2hv.at
info@b2hv.at



Zertifikat Nr. 20 100 92003758

DHV1233 Rev00
ENGLISH

Subject to alternations –
errors excepted
Illustrations are not binding

BA60

Portable Oil Test Set

The BA Breakdown Analyzer is the smallest and lightest portable oil test set its rating available. The 2.8" colour display (OLED) is very bright and offers an optimal readability even for outdoor use.

For testing modern silicon, mineral and ester oils a very fast switch-off time after flash over is crucial. The BA has the fastest switch-off time on the market available (<5 µs).

With the PC Software "BA Control Center" individual test procedures can be programmed and several units can be controlled and overviewed simultaneously.

Test results are available as pdf files and as text files.

The unit has USB Flash Drive and a Bluetooth connection for communications between the test unit and the PC.



Type	BA60
Article number	SB0006
Output Voltage	Up to 60 kV rms symmetrical
Voltage measurement accuracy	±1 kV
Voltage rise rate	0.5 ... 10 kV/s
Resolution (displayed)	0.1 kV
Power supply	85 V ... 264 V (47 Hz ... 63 Hz)
Power consumption	60 VA
Switch-off time on flashover	< 5 µs
Measurement of oil temperature	0 ... 100 °C
Temperature resolution	1 °C
Display	2.8" colour (ultra bright)
Selectable programs	VDE370-5/96, ÖVE EN 60156, IEC 60156/95, ASTM1816-04-1, ASTM1816-04-2, ASTM877-02A, ASTM977-02B, AS1767.2.1, BS EN60156, NEN 10 156, NF EN60156, PA SEV EN60156, SABS EN60156, UNE EN60156, single measurement, other standards possible
Customer-specific programs	unlimited
PC Software "BA Control Center"	included
Interface	Bluetooth
USB	USB memory stick
Operating temperature	-5° ... +45 °C
Storage temperature	-20° ... +60 °C
Relative humidity	Non condensing
Dimensions W x H x D	430 x 280 x 250 mm
Weight	19 kg
Delivery includes	Breakdown Analyzer BA, Test vessel with electrodes, PC Software "BA Control Center", Lifting stick for magnetic stirrer, Magnetic oil stirrer, Setting gauge 2.5 mm IEC, User manual,

	Article Number		Article Number
Test vessel IEC60 156 with cover and electrodes	GB0050	Rugged Transport box	VKR0010
Test vessel IEC 60 156 with cover and electrodes	GB0051	Transport bag	VKR0011
Test vessel ASTM D 877 with cover and electrodes	GB0052	Dust cover	VKR0016
Test vessel ASTM D 1816-04 with cover and electrodes	GB0053	Setting gauge 1 or 2 or 2.5 or 4 or 5 mm	GB0110-0114
		Ring nut wrench (test vessel)	GB0106